

MAXI-TUFF[®]

ELEVATOR BUCKETS

THE #1 SELLING INDUSTRIAL BUCKET IN THE WORLD



**OUT-LASTS, OUT-PERFORMS
AND OUT-SELLS THE "COMPETITION".**

Maxi-Lift Inc.[®]

MAXILIFT.COM

**ONETUFF
BUCKET**

Maxi-Tuff® AA / Tiger-Tuff® Industrial Elevator Buckets

Slow Speed Centrifugal Discharge 125-450 FPM



The Maxi-Tuff AA centrifugal elevator bucket has the traditional shape of a cast iron bucket. This bucket has a heavy reinforced lip and corners with a thickened back wall for mounting strength. Standard spacing is projection x 2. The most common applications include handling stone, sand, gravel, coal, fertilizer, clay, salt, limestone and cement. The Maxi-Tuff AA bucket is the best bucket for tough, abrasive industrial applications.

Maxi-Tuff® Industrial Duty AA Buckets

BUCKET SIZE, INCHES**					WEIGHT, LBS.			CAPACITY				
Bucket Size	Length	Proj.	Depth	Backwall Thickness	(Poly) H.D.P.E.	Nylon	Urethane	Water Level Cu. Inches X-X	100% Gross Capacity Cu. Inches X-Y	Capacity Cu. Feet X-X	Standard Spacing	Carton Qty
4 x 3	4-1/4	3-1/8	3-1/8	0.205	0.18	0.20	0.24	13.40	15.90	0.008	6	24
5 x 4	5-1/4	4-1/8	4-1/8	0.205	0.44	0.51	0.60	34.80	45.20	0.020	8	24
6 x 4	6-1/4	4-1/8	4-1/8	0.205	0.49	0.56	0.69	41.50	54.30	0.024	8	24
7 x 4	7-1/4	4-1/8	4-1/8	0.225	0.56	0.65	0.78	51.30	65.30	0.030	8	24
7 x 5	7-1/8	5-1/8	5-1/4	0.325	0.82	0.93	1.14	76.60	94.60	0.044	10	24
8 x 5	8-1/8	5-1/8	5-1/4	0.325	1.02	1.17	1.40	89.70	111.70	0.052	10	28
9 x 5	9-1/8	5-1/8	5-1/4	0.320	1.02	1.17	1.41	101.30	122.00	0.059	10	28
9 x 6	9-3/8	6-1/8	6-1/8	0.290	1.23	1.45	1.72	132.40	170.90	0.077	12	42
10 x 6	10-3/8	6-1/8	6-1/8	0.322	1.39	1.54	1.88	148.30	191.60	0.086	12	35
11 x 6	11-3/8	6-1/8	6-1/8	0.285	1.43	1.63	1.99	163.50	209.30	0.095	12	35
12 x 6	12-3/8	6-1/8	6-1/8	0.345	1.95	2.21	2.62	186.10	248.10	0.108	12	24
12 x 7	12-3/8	7-1/8	7-1/8	0.284	2.21	2.47	3.00	244.10	320.40	0.141	14	12
14 x 7	14-3/8	7-1/8	7-1/8	0.300	2.57	2.91	3.50	298.40	384.40	0.173	14	12
14 x 8	14-3/8	8-1/8	8-1/8	0.455	3.64	4.12	4.93	351.50	463.80	0.204	16	12
16 x 8	16-3/8	8-1/8	8-1/8	0.455	4.12	4.62	5.58	406.40	540.10	0.235	16	10
18 x 8	18-1/8	8-1/8	8-1/8	0.455	4.52	5.24	6.09	467.40	619.40	0.271	16	10
18 x 10	18-1/2	10-1/8	10-1/8	0.463	6.83	7.80	9.40	692.60	915.30	0.401	20	7



The Tiger-Tuff Industrial is a maximum duty industrial elevator bucket, designed and engineered to maximize bucket life and elevated capacity. This will reduce down time and lower maintenance costs. The Tiger-Tuff Industrial bucket has the thickest lip, back wall and corners to maximize bucket life and maintain capacity. Standard spacing is projection x 2. The most common applications include aggregate, sand, gravel, coal, gypsum, limestone, clay, cement and many, many more. The Tiger-Tuff Industrial is the maximum duty industrial bucket for your most demanding industrial applications.

Tiger-Tuff® Industrial Duty Buckets

BUCKET SIZE, INCHES**					WEIGHT, LBS.		CAPACITY				
Bucket Size	Length	Proj.	Depth	Backwall Thickness	Nylon	Urethane	Water Level Cu. Inches X-X	100% Gross Capacity Cu. Inches X-Y	Capacity Cu. Feet X-X	Standard Spacing	Carton Qty
12 x 7	12-1/2	7-3/4	7	0.43	3.92	4.26	269.24	344.58	0.156	14	7
13 x 7	13-1/2	7-3/4	7	0.43	4.22	4.59	292.51	375.4	0.169	14	7
14 x 7	14-1/2	7-3/4	7	0.43	4.49	4.88	315.77	404.19	0.183	14	7
15 x 7	15-1/2	7-3/4	7	0.43	4.63	5.05	346.64	443.63	0.201	14	7
16 x 7	16-1/2	7-3/4	7	0.43	4.77	5.18	377.41	483.08	0.218	14	7
12 x 8	12-5/8	8-3/4	8-1/4	0.43	5.08	6.03	373.00	477.44	0.216	16	6
13 x 8	13-5/8	8-3/4	8-1/4	0.43	5.16	6.46	404.85	518.21	0.234	16	6
14 x 8	14-5/8	8-3/4	8-1/4	0.43	5.55	6.60	436.80	559.10	0.253	16	6
16 x 8	17	9-1/16	8-1/8	0.50	6.18	7.51	512.57	656.09	0.297	18	10
18 x 8	19	9-1/16	8-1/8	0.50	6.91	8.08	567.49	726.39	0.328	18	10
20 x 8	21	9-1/16	8-1/8	0.50	7.51	8.80	646.81	827.92	0.374	18	10
22 x 8	23	9-1/4	8-1/4	0.50	9.23	11.02	701.90	898.43	0.406	18	6
24 x 8	25	9-1/4	8-1/4	0.50	9.55	11.48	763.40	977.15	0.441	18	6
16 x 10	17	11	10	0.60	10.03	12.24	795.70	1018.50	0.461	20	6
18 x 10	19	11	10	0.60	11.13	13.58	910.00	1164.80	0.527	20	6
20 x 10	21	11	10	0.60	12.05	14.42	1032.50	1321.60	0.598	20	6

** Actual dimensions may vary slightly on all elevator buckets, depending on specified raw material.

Ask about our 3 FOR FREE sample program!



◀ NYLON
Color: Tan
Made for Hot, Abrasive, Dense Products.



◀ URETHANE
Color: Green
FDA approved.
Made for Abrasive, Sticky and Sharp Materials.



◀ POLYETHYLENE
Color: White
FDA approved.
Made for Food Grade Products.

Call: 1-800-527-0657 or Visit Us Online at: www.maxilift.com
16400 Midway Rd Dallas, TX 75001 • Ph: (972)735-8855 Fx: (972)735-8896 • info@maxilift.com